

Package: rcrisp (via r-universe)

September 22, 2026

Title Automate the Delineation of Urban River Spaces

Version 0.3.1

Description Provides tools to automate the morphological delineation of riverside urban areas based on a method introduced in Forgaci (2018) <[doi:10.7480/abe.2018.31](https://doi.org/10.7480/abe.2018.31)>. Delineation entails the identification of corridor boundaries, segmentation of the corridor, and delineation of the river space using two-dimensional spatial information from street network data and digital elevation data in a projected CRS. The resulting delineation can be used to characterise spatial phenomena that can be related to the river as a central element.

License Apache License (>= 2)

URL <https://cityriverspaces.github.io/rcrisp/>,
<https://github.com/CityRiverSpaces/rcrisp>,
<https://doi.org/10.5281/zenodo.15793526>

BugReports <https://github.com/CityRiverSpaces/rcrisp/issues>

Depends R (>= 4.1.0)

Imports checkmate, cli, dbscan, dplyr, lwgeom, osmdata, rcoins, rlang, rstac, sf (>= 0.9.0), sfheaders, sfnetworks, stringr, terra, tidygraph, units, visor

Suggests autotest, ggplot2, knitr, purrr, rmarkdown, testthat (>= 3.0.0), withr

Additional_repositories <https://ropensci.r-universe.dev>

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE, roclets = c("` namespace", "` rd", "` srr::srr_stats_roclet"))

RoxygenNote 7.3.2

Config/pak/sysreqs libabsl-dev cmake libgdal-dev gdal-bin libgeos-dev libglpk-dev libicu-dev libjpeg-dev libpng-dev libxml2-dev libssl-dev libproj-dev libsqlite3-dev libudunits2-dev

Repository <https://ropensci-staging.r-universe.dev>

Date/Publication 2026-09-22 12:31:05 UTC

RemoteUrl <https://github.com/CityRiverSpaces/rcrisp>

RemoteRef HEAD

RemoteSha eaa9fc71646819982e6b553becd056c20c402ed6

Contents

as_bbox	3
as_crs	3
as_network	4
bucharest_dambovita	5
cache_directory	6
check_cache	6
clean_network	7
clear_cache	7
default_stac_dem	8
define_aoi	9
delineate	10
delineate_city_river	12
delineate_corridor	13
delineate_riverspace	14
delineate_segments	15
delineate_valley	16
delineation	17
flatten_network	17
geom_delineation	18
get_dem	19
get_dem_example_data	20
get_osm	21
get_osm_bb	22
get_osm_buildings	23
get_osm_city_boundary	23
get_osm_example_data	24
get_osm_railways	25
get_osm_river_centerline	25
get_osm_river_surface	26
get_osm_streets	27
get_river_aoi	28
get_stac_asset_urls	29
get_utm_zone	29
load_dem	30
osmdata_as_sf	31
plot.delineation	31

as_bbox

3

print.delineation

32

print.summary.delineation

33

reproject

33

summary.delineation

34

Index

36

as_bbox

Get the bounding box from the x object

Description

If the x does not have a CRS, WGS84 is assumed.

Usage

```
as_bbox(x)
```

Arguments

x

Simple feature object (or compatible) or a bounding box, provided either as a matrix (with x, y as rows and min, max as columns) or as a vector (xmin, ymin, xmax, ymax)

Value

A bbox object as returned by `sf::st_bbox()`

Examples

```
library(sf)
bounding_coords <- c(25.9, 44.3, 26.2, 44.5)
bb <- as_bbox(bounding_coords)
class(bb)
st_crs(bb)
```

as_crs

Standardise the coordinate reference system (CRS) of an object

Description

Standardise the coordinate reference system (CRS) of an object

Usage

```
as_crs(x, allow_geographic = FALSE)
```

Arguments

- x** An object of class `sf`, `sfc`, `bbox`, or a numeric or character vector representing a CRS (e.g., EPSG code). If numeric, the value should be an unrestricted positive number representing a valid EPSG code.
- allow_geographic** Logical, whether to allow geographic CRS (lat/lon).

Value

An object of class `sf::crs` with a valid CRS.

Examples

```
library(sf)

# Standardise a numeric EPSG code
as_crs(4326, allow_geographic = TRUE)

# Standardise a character EPSG code
as_crs("EPSG:4326", allow_geographic = TRUE)

# Standardise a bbox object
bb <- st_bbox(c(xmin = 25.9, ymin = 44.3, xmax = 26.2, ymax = 44.5),
              crs = 4326)
as_crs(bb, allow_geographic = TRUE)

# Standardise a simple feature object
bb_sfc <- st_as_sfc(bb)
bb_sf <- st_as_sf(bb_sfc)
as_crs(bb_sf, allow_geographic = TRUE)
as_crs(bb_sfc, allow_geographic = TRUE)
```

as_network

Create a network from a collection of line strings

Description

Create a network from a collection of line strings

Usage

```
as_network(edges, flatten = TRUE, clean = TRUE, na_action = "warn")
```

Arguments

- edges** An `sf::sf` or `sf::sfc_LINESTRING` object with the network edges
- flatten** Whether all intersections between edges should be converted to nodes

<code>clean</code>	Whether general cleaning tasks should be run on the generated network (see clean_network() for the description of tasks)
<code>na_action</code>	A case-insensitive character string specifying how to deal with missing values in non-geometry columns of edges. Possible values: • "warn" (default): issue a warning if any NA values are found. • "error": stop with an error if any NA values are found. • "ignore": silently proceed without checking for NA values • "impute": replace NA values before building the network. For character columns, NAs are replaced with "unknown"; for numeric columns, NAs are replaced with the column median.

Value

An `sfnetworks::sfnetwork` object

Examples

```
edges <- sf::st_sfc(
  sf::st_linestring(matrix(c(0, 0, 1, 1), ncol = 2, byrow = TRUE)),
  sf::st_linestring(matrix(c(0, 1, 1, 0), ncol = 2, byrow = TRUE)),
  crs = sf::st_crs("EPSG:32635")
)

# Run with default values
as_network(edges)

# Only build the spatial network
as_network(edges, flatten = FALSE, clean = FALSE)
```

`bucharest_dambovita` *rcrisp example delineation data for Bucharest*

Description

Delineation generated with `rcrisp` example data found at <https://zenodo.org/records/16325879>

Usage

```
bucharest_dambovita
```

Format

A list of `sf` objects representing:

valley The valley boundaries of river Dâmbovița.
corridor The corridor boundaries of river Dâmbovița.
segments Corridor segments of river Dâmbovița.
riverspace River space of Dâmbovița.

cache_directory	<i>Return the cache directory used by the package</i>
-----------------	---

Description

By default, the user-specific directory as returned by `tools::R_user_dir()` is used. A different directory can be used by setting the environment variable `CRISP_CACHE_DIRECTORY`. This can also be done by adding the following line to the `.Renv` file: `CRISP_CACHE_DIRECTORY=/path/to/crip/cache/dir`.

Usage

```
cache_directory()
```

Value

The cache directory used by `rcrisp`.

Examples

```
cache_directory()
```

check_cache	<i>Check cache</i>
-------------	--------------------

Description

A message is displayed if the cache size is > 100 MB or if it includes files older than 30 days.

Usage

```
check_cache()
```

Value

NULL

Examples

```
check_cache()
```

clean_network	<i>Clean a spatial network</i>
---------------	--------------------------------

Description

Subdivide edges by **adding missing nodes**, (optionally) simplify the network (see [simplify_network\(\)](#)), remove **pseudo-nodes**, and discard all but the main connected component.

Usage

```
clean_network(network, simplify = TRUE)
```

Arguments

network	A network object of class sfnetworks::sfnetwork
simplify	Whether the network should be simplified with simplify_network()

Value

A cleaned network object of class [sfnetworks::sfnetwork](#)

Examples

```
bucharest_osm <- get_osm_example_data()
edges <- dplyr::bind_rows(bucharest_osm$streets,
                          bucharest_osm$railways)
network <- sfnetworks::as_sfnetwork(edges, directed = FALSE)
clean_network(network)
```

clear_cache	<i>Remove cache files</i>
-------------	---------------------------

Description

Remove files from cache directory either before a given date or entirely.

Usage

```
clear_cache(before_date = NULL)
```

Arguments

before_date	Date before which cache files should be removed provided as object of class Date or as a case dependent character vector accepted by as.Date()
-------------	--

Value

NULL

Examples

```
# Clear all cache
clear_cache()

# Clear cache before given date
before_date <- as.Date("1-1-1999", "%m-%d-%Y")
clear_cache(before_date = before_date)
```

default_stac_dem	<i>Default STAC collection</i>
------------------	--------------------------------

Description

Endpoint and collection ID of the default STAC collection where to access digital elevation model (DEM) data. This is the global Copernicus DEM 30 dataset hosted on AWS, as listed in the EarthSearch STAC API endpoint. Note that AWS credentials need to be set up in order to access the data (not the catalog). References:

- [EarthSearch STAC API](#)
- [Copernicus DEM](#)
- [AWS Copernicus DEM datasets](#)
- [Data license](#)

Usage

```
default_stac_dem
```

Format

An object of class `list` of length 2.

define_aoi	<i>Define delineation parameters within an area of interest</i>
------------	---

Description

Define delineation parameters within an area of interest

Usage

```
define_aoi(
  city_name,
  river_name,
  crs = NULL,
  network_buffer = 3000,
  dem_buffer = 2500,
  buildings_buffer = 100
)
```

Arguments

city_name	A character vector of length one
river_name	A character vector of length one
crs	The projected Coordinate Reference System (CRS) to use. If not provided, the suitable Universal Transverse Mercator (UTM) CRS is selected
network_buffer	Add a buffer (an integer in meters) around river to retrieve additional data (streets, railways, etc.). Default is 3000 m.
dem_buffer	Size of the buffer region (in meters) around the spatial network to retrieve the DEM.
buildings_buffer	Add a buffer (an integer in meters) around the river to retrieve additional data (buildings). Default is 100 m.

Value

A list with delineation parameter values, namely city_name and river_name as character vectors of length one, bb as object of class `sf::bbox`, crs as object of class `sf::crs`, and network_buffer, dem_buffer and buildings_buffer as numerical vector of length one.

Examples

```
# Get default parameters in AOI
aoi <- define_aoi("Bucharest", "Dâmbovița")

# Get parameters in AOI with custom CRS
aoi <- define_aoi("Bucharest", "Dâmbovița",
  crs = "EPSG:3844") # National projected CRS
```

```
# Get parameters in AOI with non-default buffers
aoi <- define_aoi("Bucharest", "Dâmbovița",
  network_buffer = 2000,
  dem_buffer = 2000,
  buildings_buffer = 150)
```

delineate

Delineate a corridor around a river

Description

Given a set of delineation parameters and input data, carry out corridor delineation, corridor segmentation and/or riverspace delineation as indicated by the user.

Usage

```
delineate(
  aoi,
  osm,
  dem = NULL,
  corridor_init = "valley",
  max_iterations = 10,
  capping_method = "shortest-path",
  angle_threshold = 100,
  corridor = TRUE,
  segments = FALSE,
  riverspace = FALSE
)
```

Arguments

- | | |
|---------------|--|
| aoi | A list of delineation parameters for an area of interest, namely \$city_name, \$river_name, \$crs, \$network_buffer, \$dem_buffer, and \$buildings_buffer. For more info see define_aoi() . |
| osm | A list with OpenStreetMap data sets within the aoi, as objects of class sf::sfc |
| dem | Digital elevation model (DEM) of the region (only used if corridor_init is "valley") |
| corridor_init | How to estimate the initial guess of the river corridor. It can take the following values: <ul style="list-style-type: none"> • "valley": use the river valley boundary, as estimated from a Digital Elevation Model (DEM) (for more info see delineate_valley()) • numeric or integer: use a buffer region of the given size (in meters) around the river centerline • An sf::sf or sf::sfc object: use the given input geometry |

<code>max_iterations</code>	Maximum number of iterations employed to refine the corridor edges (see <code>corridor_edge()</code>).
<code>capping_method</code>	The method employed to connect the corridor edge end points (i.e., to "cap" the corridor), as character vector of length one. See <code>cap_corridor()</code> for the available methods.
<code>angle_threshold</code>	Only network edges forming angles above this threshold (in degrees) are considered when forming segment edges. See <code>delineate_segments()</code> and <code>rcoins::stroke()</code> . Only used if <code>segments</code> is TRUE.
<code>corridor</code>	Whether to carry out the corridor delineation
<code>segments</code>	Whether to carry out the corridor segmentation
<code>riverspace</code>	Whether to carry out the riverspace delineation

Details

The returned `delineation` class is a list wrapping objects of class `sf::sfc_POLYGON` or `sf::sfc_MULTIPOLYGON` which can be retrieved through subsetting and converted to other common spatial classes in typical sf- or terra-based workflows.

Corridor delineation depends on the availability of OpenStreetMap street and railway data around the river. Sparse OSM data, especially too few river crossings, may lead to failed delineation.

Value

A list object of class `delineation` containing zero or more of the following elements: "valley", "corridor", "segments", and "riverspace", each as an `sf::sfc_POLYGON` or `sf::sfc_MULTIPOLYGON` object (depending on the geometry of the input data). The list contains only the geometries corresponding to the delineation steps that were carried out (e.g., if `segments` is FALSE, the list will not contain a "segments" element). In any case, the returned object also contains the base layers and a list `aoi` with the parameters used for delineation.

Examples

```
# Define delineation parameters within area of interest
aoi <- define_aoi("Bucharest", "Dâmbovița")

# Get data
osm <- get_osm(aoi)
dem <- get_dem(aoi, osm)

# Delineate with defaults
delineate(aoi, osm, dem)

# Carry out all delineations
delineate(aoi, osm, dem, segments = TRUE, riverspace = TRUE)
```

delineate_city_river	<i>Delineate a corridor around a river</i>
----------------------	--

Description

This is a convenience function used for quick delineation. With only the city name and river name as input, it uses default delineation parameters, it retrieves OSM and DEM data and returns a list with all three delineations.

Usage

```
delineate_city_river(  
  city_name,  
  river_name,  
  corridor = TRUE,  
  segments = TRUE,  
  riverspace = TRUE  
)
```

Arguments

city_name	A character vector of length one.
river_name	A character vector of length one.
corridor	Whether to carry out the corridor delineation. Default is TRUE.
segments	Whether to carry out the corridor segmentation. Default is TRUE.
riverspace	Whether to carry out the riverspace delineation. Default is TRUE.

Value

A list with the valley, corridor, segments, and riverspace geometries as `sf::sf_POLYGON` objects.

Examples

```
delineate_city_river("Bucharest", "Dâmbovița")
```

delineate_corridor *Delineate a river corridor on a spatial network*

Description

The corridor edges on the two river banks are drawn on the provided spatial network starting from an initial guess of the corridor (based e.g. on the river valley).

Usage

```
delineate_corridor(
  network,
  river,
  corridor_init = 1000,
  max_width = 3000,
  max_iterations = 10,
  capping_method = "shortest-path"
)
```

Arguments

network	The spatial network of class <code>sfnetworks::sfnetwork</code> to be used for the delineation. Required, no default.
river	A (MULTI)LINESTRING simple feature geometry of class <code>sf::sf</code> or <code>sf::sfc</code> representing the river centerline. Required, no default.
corridor_init	How to estimate the initial guess of the river corridor. It can take the following values: • numeric or integer: use a buffer region of the given size (in meters, positive, unrestricted) around the river centerline • An <code>sf::sf</code> or <code>sf::sfc</code> object: use the given input geometry
max_width	A positive number representing the (approximate) maximum width of the corridor in meters. The upper limit is unrestricted. The spatial network is trimmed by a buffer region of this size around the river.
max_iterations	A positive integer greater than 0, with upper limit unrestricted, representing the maximum number of iterations employed to refine the corridor edges (see <code>corridor_edge()</code>).
capping_method	Case-insensitive character vector of length 1 with the method employed to connect the corridor edge end points (i.e. to "cap" the corridor). See <code>cap_corridor()</code> for the available methods.

Value

A simple feature geometry of class `sf::sfc_POLYGON` representing the river corridor

Examples

```

bucharest_osm <- get_osm_example_data()
streets <- bucharest_osm$streets
railways <- bucharest_osm$railways
river <- bucharest_osm$river_centerline

# Delineate with default values
network <- rbind(streets, railways) |> as_network()
delineate_corridor(network = network, river = river)

# Delineate with user-specified parameters
bucharest_dem <- get_dem_example_data()
corridor_init <- delineate_valley(dem = bucharest_dem, river = river)
delineate_corridor(network = network, river = river,
  corridor_init = corridor_init,
  max_width = 4000, max_iterations = 5,
  capping_method = "direct")

```

delineate_riverspace *Delineate the space surrounding a river*

Description

Delineate the space surrounding a river

Usage

```

delineate_riverspace(
  river,
  occluders = NULL,
  density = 1/50,
  ray_num = 40,
  ray_length = 100
)

```

Arguments

river	List with river surface and centerline
occluders	Geometry of occluders
density	Density of viewpoints
ray_num	Number of rays as numeric vector of length one
ray_length	Length of rays in meters as numeric vector of length one

Details

For riverspace delineation, OSM water polygons intersecting the river centerline are treated as part of the river, including connected water bodies such as lakes and reservoirs. Viewpoints are calculated from water edges where available, and from the river centerline when river surface polygons are missing or partial.

Value

Riverspace as object of class `sf::sfc_POLYGON`

Examples

```
bucharest_osm <- get_osm_example_data()
delineate_riverspace(bucharest_osm$river_surface, bucharest_osm$buildings)
```

delineate_segments	<i>Split a river corridor into segments</i>
--------------------	---

Description

Segments are defined as corridor subregions separated by river-crossing transversal lines that form continuous strokes in the network.

Usage

```
delineate_segments(corridor, network, river, angle_threshold = 100)
```

Arguments

corridor	The river corridor as a simple feature geometry of class <code>sfc_POLYGON</code>
network	The spatial network of class <code>sfnetwork</code> to be used for the segmentation
river	The river centerline as a simple feature geometry of class <code>sf::sf</code> or <code>sf::sfc</code>
angle_threshold	Only consider angles above this threshold (in degrees) to form continuous strokes in the network. The value can range between 0 and 180, with the default set to 100. See <code>rcoins::stroke()</code> for more details.

Value

Segment polygons as a simple feature geometry of class `sf::sfc_POLYGON`

Examples

```
bucharest_osm <- get_osm_example_data()
corridor <- bucharest_dambovita$corridor
network <- rbind(bucharest_osm$streets, bucharest_osm$railways) |>
  as_network()
river <- bucharest_osm$river_centerline
delineate_segments(corridor, network, river)
```

delineate_valley

Extract the river valley from the DEM

Description

The slope of the digital elevation model (DEM) is used as friction (cost) surface to compute the cost distance from any grid cell of the raster to the river. A characteristic value (default: the mean) of the cost distance distribution in a region surrounding the river (default: a buffer region of 2 km) is then calculated, and used to threshold the cost-distance surface. The resulting area is then "polygonized" to obtain the valley boundary as a simple feature geometry.

Usage

```
delineate_valley(dem, river)
```

Arguments

dem	SpatRaster object with the digital elevation model of the region
river	An object of class <code>sf::sf</code> or <code>sf::sfc</code> representing the river

Value

River valley as a simple feature geometry of class `sfc_MULTIPOLYGON`

Examples

```
bucharest_osm <- get_osm_example_data()
bucharest_dem <- get_dem_example_data()
delineate_valley(bucharest_dem, bucharest_osm$river_centerline)
```

delineation	<i>The delineation class</i>
-------------	------------------------------

Description

An S3 class representing the result of a delineation as returned by `delineate()`.

Value

An object of class `delineation` containing zero or more of the spatial layers `$valley`, `$corridor`, `$segments`, and `$riverspace` (each an `sf::sfc_POLYGON` or `sf::sfc_MULTIPOLYGON` object), plus the base OSM and optionally DEM layers and an `$aoi` list with the delineation parameters produced by `define_aoi()`. See `delineate()` for details.

Examples

```
bd <- delineate_city_river("Bucharest", "Dâmbovița")
class(bd)
```

flatten_network	<i>Flatten a network by adding points at apparent intersections</i>
-----------------	---

Description

All crossing edges are identified, and the points of intersections are injected within the edge geometries. Note that the injected points are not converted to network nodes (this can be achieved via `sfnetworks::to_spatial_subdivision()`, which is part of the tasks that are included in `clean_network()`).

Usage

```
flatten_network(network)
```

Arguments

network	A network object of class <code>sfnetworks::sfnetwork</code>
---------	--

Details

The functionality is similar to `sfnetworks::st_network_blend()`, but in that case an external point is only injected to the closest edge.

Value

An `sfnetworks::sfnetwork` object with additional points at intersections

Examples

```
bucharest_osm <- get_osm_example_data()
edges <- dplyr::bind_rows(bucharest_osm$streets,
                          bucharest_osm$railways)
network <- sfnetworks::as_sfnetwork(edges, directed = FALSE)
flatten_network(network)
```

geom_delineation	<i>ggplot2 layer for a delineation object</i>
------------------	---

Description

Creates a list of `ggplot2::geom_sf()` layers representing the delineation results of a delineation object. The list can be added to a `ggplot2::ggplot()` object with `+`, and further layers or themes can be added on top. Base layers (`streets`, `railways`, `river_centerline`, `river_surface`) are not included and can be added separately with `ggplot2::geom_sf()`.

Usage

```
geom_delineation(x, extent = "corridor", legend = TRUE)
```

Arguments

<code>x</code>	An object of class <code>delineation</code> . This is typically the output of the <code>delineate()</code> function.
<code>extent</code>	The delineation layer whose bounding box sets the plot extent. One of "corridor", "valley", "riverspace", or NULL (no restriction, ggplot2 fits all layers). Defaults to "corridor".
<code>legend</code>	Whether the plot should display a legend. Default is TRUE.

Details

The following layers are included (where present in `x`), in the following order:

- corridor or riverspace (only when corridor is absent): drawn first to set the plot extent
- valley: light grey, transparent fill, no outlines
- segments: outlined polygons
- corridor: outlined polygon

Value

A list of `ggplot2::geom_sf()` and `ggplot2::coord_sf()` elements to be added to a `ggplot2::ggplot()` object.

See Also

[plot.delineation\(\)](#) for a base R alternative.

Examples

```
library(ggplot2)
bd <- delineate_city_river("Bucharest", "Dâmbovița")
ggplot() + geom_delineation(bd) + theme_void()
ggplot() + geom_delineation(bd, extent = "valley") + theme_void()
```

get_dem

*Access digital elevation model (DEM) for a given region***Description**

Access digital elevation model (DEM) for a given region

Usage

```
get_dem(
  aoι,
  osm,
  dem_source = "STAC",
  stac_endpoint = NULL,
  stac_collection = NULL,
  force_download = FALSE
)
```

Arguments

aoι	A list of delineation parameters, including \$dem_buffer used to expand the area of interest covered by the network and \$crs for the CRS which to transform the DEM to
osm	A list with OpenStreetMap data sets for the a location, as objects of class sf::sfc
dem_source	Source of the DEM: • If "STAC" (default), DEM tiles are searched on a SpatioTemporal Asset Catalog (STAC) end point, then accessed and mosaicked to the area of interest
stac_endpoint	URL of the STAC API endpoint (only used if dem_source is "STAC"). For more info, see get_stac_asset_urls()
stac_collection	Identifier of the STAC collection to be queried (only used if dem_source is "STAC"). For more info, see get_stac_asset_urls()
force_download	Download data even if cached data is available

Value

DEM as a terra SpatRaster object

Examples

```
# Define delineation parameters and get OSM data within area of interest
aoi <- define_aoi("Bucharest", "Dâmbovița")
osm <- get_osm(aoi)

# Get DEM with default values
dem <- get_dem(aoi, osm)

# Get DEM from custom STAC endpoint
get_dem(aoi, osm,
        stac_endpoint = "some endpoint",
        stac_collection = "some collection")

# Specify CRS
get_dem(bb, crs = crs)
```

get_dem_example_data *Get example DEM data*

Description

This function retrieves example Digital Elevation Model (DEM) data from the Zenodo data repository, and it can be used in examples and tests. The code used to generate the example dataset is available at <https://github.com/CityRiverSpaces/CRIspExampleData>. Note that the example dataset is cached locally, so that subsequent calls to the function can load the example data from disk without having to re-download the data.

Usage

```
get_dem_example_data(force_download = FALSE)
```

Arguments

force_download Download data even if cached data is available

Value

An object of class `terra::SpatRaster` containing the DEM data.

Examples

```
get_dem_example_data(force_download = TRUE)
```

`get_osm`*Retrieve OpenStreetMap data for a given location*

Description

Retrieve OpenStreetMap data for a given location, including the city boundary, the river centreline and surface, the streets, the railways, and the buildings

Usage

```
get_osm(  
  aoi,  
  city_boundary = TRUE,  
  network = TRUE,  
  buildings = TRUE,  
  force_download = FALSE  
)
```

Arguments

<code>aoi</code>	A list of delineation parameters
<code>city_boundary</code>	A logical indicating if the city boundary should be retrieved. Default is TRUE.
<code>network</code>	A logical indicating if the spatial network should be retrieved. Default is TRUE.
<code>buildings</code>	A logical indicating if buildings should be retrieved. Default is TRUE.
<code>force_download</code>	Download data even if cached data is available

Value

A list with the retrieved OpenStreetMap data sets for the given location, as objects of class `sf::sfc`

Examples

```
# Set parameters  
city <- "Bucharest"  
river <- "Dâmbovița"  
  
# Define AOI parameters  
aoi <- define_aoi(city, river)  
  
# Get OSM data with defaults  
get_osm(aoi)  
  
# Get OSM data without city boundary  
get_osm(aoi, city_boundary = FALSE)  
  
# Use custom network buffer to get streets and railways  
aoi2 <- aoi
```

```
aoi2$network_buffer = 3500
get_osm(aoi2)

# Use custom buffer to get buildings
aoi3 <- aoi
aoi3$buildings_buffer = 150
get_osm(aoi3)

# Use custom CRS
aoi4 <- aoi
aoi4$crs <- "EPSG:31600"
get_osm(aoi4)

# Avoid getting OSM data from cache
get_osm(city_name = city, river_name = river, force_download = TRUE)
```

get_osm_bb	<i>Get the bounding box of a city</i>
------------	---------------------------------------

Description

Get the bounding box of a city

Usage

```
get_osm_bb(city_name)
```

Arguments

city_name	A character vector of length one
-----------	----------------------------------

Value

A bbox object with the bounding box of the city

Examples

```
get_osm_bb(city_name = "Bucharest")
```

get_osm_buildings	<i>Get OpenStreetMap buildings</i>
-------------------	------------------------------------

Description

Get buildings from OpenStreetMap within a given buffer around a river.

Usage

```
get_osm_buildings(aoi, crs = NULL, force_download = FALSE)
```

Arguments

aoi	Area of interest as sf object or bbox
crs	Coordinate reference system as EPSG code
force_download	Download data even if cached data is available

Value

An object of class `sf::sf_POLYGON`

Examples

```
bb <- get_osm_bb("Bucharest")
crs <- get_utm_zone(bb)
get_osm_buildings(aoi = bb, crs = crs)
```

get_osm_city_boundary	<i>Get the city boundary from OpenStreetMap</i>
-----------------------	---

Description

This function retrieves the city boundary from OpenStreetMap based on a bounding box with the OSM tags "place:city" and "boundary:administrative". The result is filtered by the city name.

Usage

```
get_osm_city_boundary(
  bb,
  city_name,
  crs = NULL,
  multiple = FALSE,
  force_download = FALSE
)
```

Arguments

bb	Bounding box of class bbox
city_name	A case-sensitive character vector of length 1 with the name of the city
crs	Coordinate reference system as EPSG code
multiple	A logical indicating if multiple city boundaries should be returned. By default, only the first one is returned.
force_download	Download data even if cached data is available

Value

An object of class `sf::sfc_POLYGON` or `sf::sfc_MULTIPOLYGON` with the city boundary

Examples

```
bb <- get_osm_bb("Bucharest")
crs <- get_utm_zone(bb)
get_osm_city_boundary(bb = bb, city_name = "Bucharest", crs = crs)
```

`get_osm_example_data` *Get example OSM data*

Description

This function retrieves example OpenStreetMap (OSM) data from the Zenodo data repository, and it can be used in examples and tests. The code used to generate the example dataset is available at <https://github.com/CityRiverSpaces/CRiSpExampleData>. Note that the example dataset is cached locally, so that subsequent calls to the function can load the example data from disk without having to re-download the data.

Usage

```
get_osm_example_data(force_download = FALSE)
```

Arguments

force_download Download data even if cached data is available

Value

A list of sf objects containing the OSM data as `sf::sfc` objects.

Examples

```
get_osm_example_data(force_download = TRUE)
```

get_osm_railways	<i>Get OpenStreetMap railways</i>
------------------	-----------------------------------

Description

Get OpenStreetMap railways

Usage

```
get_osm_railways(  
  aoi,  
  crs = NULL,  
  railway_values = "rail",  
  force_download = FALSE  
)
```

Arguments

aoi	Area of interest as sf object or bbox
crs	A numeric vector of length one with the EPSG code of the CRS
railway_values	A case-insensitive character vector with the railway values to retrieve.
force_download	Download data even if cached data is available

Value

An object of class `sf::sfc_LINESTRING`

Examples

```
bb <- get_osm_bb("Bucharest")  
crs <- get_utm_zone(bb)  
get_osm_railways(aoi = bb, crs = crs)
```

get_osm_river_centerline	<i>Get the river centreline from OpenStreetMap</i>
--------------------------	--

Description

Get the river centreline from OpenStreetMap

Usage

```
get_osm_river_centerline(
  bb,
  river_name,
  crs = NULL,
  buffer_distance = NULL,
  force_download = FALSE
)
```

Arguments

bb	Bounding box of class bbox
river_name	The name of the river as character vector of length 1, case-sensitive.
crs	Coordinate reference system as EPSG code
buffer_distance	Optional buffer distance in metres to expand the bounding box before cropping the river centreline. Useful when downstream processing (e.g. network or DEM analysis) extends beyond the original bb. Defaults to NULL (no expansion).
force_download	Download data even if cached data is available

Value

The river centreline as object of class `sf::sfc_LINESTRING` or `sf::sfc_MULTILINESTRING`.

Examples

```
bb <- get_osm_bb("Bucharest")
crs <- get_utm_zone(bb)
get_osm_river_centerline(bb = bb, river_name = "Dâmbovița", crs = crs,
  force_download = FALSE)
```

get_osm_river_surface *Get the river surface from OpenStreetMap*

Description

Get the river surface from OpenStreetMap

Usage

```
get_osm_river_surface(bb, river_centerline, crs = NULL, force_download = FALSE)
```

Arguments

`bb` Bounding box of class `bbox`

`river_centerline` The river centerline as an object of class `sf::sfc_LINESTRING` or `sf::sfc_MULTILINESTRING`

`crs` Coordinate reference system as EPSG code

`force_download` Download data even if cached data is available

Value

The river surface as object of class `sf::sfc_POLYGON` or `sf::sfc_MULTIPOLYGON`.

Examples

```
bb <- get_osm_bb("Bucharest")
crs <- get_utm_zone(bb)
river <- get_osm_river_centerline(bb, "Dâmbovița")
get_osm_river_surface(bb = bb, river_centerline = river, crs = crs,
  force_download = FALSE)
```

get_osm_streets	<i>Get OpenStreetMap streets</i>
-----------------	----------------------------------

Description

Get OpenStreetMap streets

Usage

```
get_osm_streets(aoi, crs = NULL, highway_values = NULL, force_download = FALSE)
```

Arguments

`aoi` Area of interest as `sf` object or `bbox`. Required, no default.

`crs` A numeric vector of length one with the EPSG code of the CRS

`highway_values` A character vector with the highway values to retrieve. If left `NULL`, the function retrieves the following values: "motorway", "trunk", "primary", "secondary", "tertiary"

`force_download` Download data even if cached data is available

Value

An object of class `sf::sfc_LINESTRING`

Examples

```
# Set parameters
bb <- get_osm_bb("Bucharest")
crs <- 31600 # National projected CRS

# Get streets with default values
get_osm_streets(aoi = bb, crs = crs)

# Specify street categories to be retrieved
get_osm_streets(aoi = bb, crs = crs, highway_values = "primary")

# Ensure that data is not retrieved from cache
get_osm_streets(aoi = bb, crs = crs, force_download = FALSE)
```

get_river_aoi	<i>Get an area of interest (AoI) around a river, cropping to the bounding box of a city</i>
---------------	---

Description

Get an area of interest (AoI) around a river, cropping to the bounding box of a city

Usage

```
get_river_aoi(river, city_bbox, buffer_distance)
```

Arguments

river	A <code>sf::sf</code> or <code>sf::sfc</code> object with the river centreline and (optionally) the river surface geometry
city_bbox	Bounding box of class <code>bbox</code> around the city
buffer_distance	A positive number representing the buffer size around the river in meters. The upper limit is unrestricted.

Value

An `sf::sfc_POLYGON` object in lat/lon coordinates

Examples

```
bb <- get_osm_bb("Bucharest")
river_centerline <- get_osm_river_centerline(bb, "Dâmbovița")
river_surface <- get_osm_river_surface(bb, "Dâmbovița")
river <- list(centerline = river_centerline, surface = river_surface)
get_river_aoi(river = river, city_bbox = bb, buffer_distance = 100)
```

get_stac_asset_urls	<i>Retrieve the URLs of all the assets intersecting a bbox from a STAC API</i>
---------------------	--

Description

Retrieve the URLs of all the assets intersecting a bbox from a STAC API

Usage

```
get_stac_asset_urls(bb, endpoint = NULL, collection = NULL)
```

Arguments

bb	A bounding box, provided either as a matrix (rows for "x", "y", columns for "min", "max") or as a vector ("xmin", "ymin", "xmax", "ymax"), in lat/lon coordinates (WGS84 coordinate reference system) of class bbox
endpoint	URL of the STAC API endpoint. To be provided together with stac_collection, or leave blank to use defaults (see default_stac_dem)
collection	Identifier of the STAC collection to be queried. To be provided together with stac_endpoint, or leave blank to use defaults (see default_stac_dem)

Value

A list of URLs for the assets in the collection overlapping with the specified bounding box

Examples

```
bb <- get_osm_bb("Bucharest")
get_stac_asset_urls(bb)

# Use non-default STAC API
get_stac_asset_urls(bb,
  endpoint = "some endpoint",
  collection = "some collection")
```

get_utm_zone	<i>Get the UTM zone of a spatial object</i>
--------------	---

Description

Get the UTM zone of a spatial object

Usage

```
get_utm_zone(x)
```

Arguments

x Object in any class accepted by [as_bbox\(\)](#)

Value

The EPSG code of the UTM zone

Examples

```
# Get EPSG code for UTM zone of Bucharest
bb <- c(xmin = 25.97, ymin = 44.33, xmax = 26.23, ymax = 44.54)
get_utm_zone(bb)
```

load_dem	<i>Retrieve DEM data from a list of STAC assets</i>
----------	---

Description

Load DEM data from a list of tiles, crop and merge using a given bounding box to create a raster DEM for the specified region. Results are cached, so that new queries with the same input parameters will be loaded from disk.

Usage

```
load_dem(bb, tile_urls, force_download = FALSE)
```

Arguments

bb A bounding box, provided either as a matrix (rows for "x", "y", columns for "min", "max") or as a vector ("xmin", "ymin", "xmax", "ymax") of class bbox.

tile_urls A list of tiles where to read the DEM data from

force_download Download data even if cached data is available

Value

A DEM of class [terra::SpatRaster](#), retrieved and retilled to the given bounding box

Examples

```
bb <- get_osm_bb("Bucharest")
tile_urls <- get_stac_asset_urls(bb)
load_dem(bb = bb, tile_urls = tile_urls, force_download = TRUE)
```

osmdata_as_sf	<i>Retrieve OpenStreetMap data as sf object</i>
---------------	---

Description

Query the Overpass API for a key:value pair within a given bounding box (provided as lat/lon coordinates). Results are cached, so that new queries with the same input parameters will be loaded from disk.

Usage

```
osmdata_as_sf(key, value, aoi, force_download = FALSE)
```

Arguments

key	A case-insensitive character vector of length 1 with the key to filter the data
value	A case-insensitive character vector with the value(s) to filter the data
aoi	An area of interest, provided either as as sf object or "bbox" or as a vector ("xmin", "ymin", "xmax", "ymax")
force_download	Download data even if cached data is available

Value

An `osmdata::osmdata` object with the retrieved OpenStreetMap data

Examples

```
bb <- get_osm_bb("Bucharest")
osmdata_as_sf(key = "highway",
              value = "motorway",
              aoi = bb,
              force_download = FALSE)
```

plot.delineation	<i>Plot a delineation object</i>
------------------	----------------------------------

Description

This S3 method provides a way to quickly visualise how the layers of a delineation object fit together using base R graphics. A delineation object typically includes the base layers streets, railways, river_centerline and river_surface, and the delineations of the valley, corridor, segments, and riverspace. Depending on the delineation object, some of the delineation layers may not be present and thus will not be plotted.

Usage

```
## S3 method for class 'delineation'
plot(x, ..., legend = TRUE)
```

Arguments

x	An object of class delineation , which is typically the output of the delineate() function.
...	Not used; included for compatibility with the generic.
legend	logical. If TRUE (default), a legend is added to the plot.

Value

NULL, invisibly. This function is called for its side effect of producing a plot.

See Also

[geom_delineation\(\)](#) for a ggplot2-based alternative.

Examples

```
bd <- delineate_city_river("Bucharest", "Dâmbovița")
plot(bd)
```

print.delineation	<i>Print a delineation object</i>
-------------------	-----------------------------------

Description

Prints a compact summary of a [delineation](#) object, showing which layers are present and their feature counts.

Usage

```
## S3 method for class 'delineation'
print(x, ...)
```

Arguments

x	An object of class delineation .
...	Not used; included for compatibility with the generic.

Value

x, invisibly.

Examples

```
bd <- delineate_city_river("Bucharest", "Dâmbovița")
print(bd)
```

```
print.summary.delineation
```

Print a summary.delineation object

Description

Print a summary.delineation object

Usage

```
## S3 method for class 'summary.delineation'
print(x, ...)
```

Arguments

x	An object of class summary.delineation, as returned by summary.delineation() .
...	Not used; included for compatibility with the generic.

Value

x, invisibly.

Examples

```
bd <- delineate_city_river("Bucharest", "Dâmbovița")
s <- summary(bd)
print(s)
```

```
reproject
```

Reproject a raster or vector dataset to the specified coordinate reference system (CRS)

Description

Reproject a raster or vector dataset to the specified coordinate reference system (CRS)

Usage

```
reproject(x, crs, ...)
```

Arguments

x	Raster (SpatRaster) or vector (sf) object
crs	CRS to be projected to, provided as numeric, integer or character vector of length one or <code>sf::crs</code> . If numeric, the value should be a positive number with unrestricted upper bound representing a valid EPSG code.
...	Optional arguments for raster or vector reproject functions

Value

`sf::sf`, `sf::sfc`, or `terra::SpatRaster` object reprojected to specified CRS

Examples

```
# Reproject a raster to EPSG:4326
r <- terra::rast(matrix(1:12, nrow = 3, ncol = 4), crs = "EPSG:32633")
reproject(r, 4326)
```

summary.delineation	<i>Summarise a delineation object</i>
---------------------	---------------------------------------

Description

Computes summary statistics for a delineation object and returns them as a structured list of class `summary.delineation`. Delineation layers are reported with their area (in km²). For segments, the number of features and mean area are also given. Base layers are reported with feature counts; `river_centerline` as total length (in km) and `river_surface` as area (in km²).

Usage

```
## S3 method for class 'delineation'
summary(object, ...)
```

Arguments

object	An object of class <code>delineation</code> .
...	Not used; included for compatibility with the generic.

Value

An object of class `summary.delineation`, which is a named list with elements `city_name`, `river_name`, `crs`, `parameters`, `delineation_layers`, and `base_layers`. `parameters` contains `network_buffer`, `dem_buffer`, and `buildings_buffer` (in metres), or NULL if no aoi was stored. Each layer entry is itself a named list of stats, or NULL if the layer is absent.

Examples

```
bd <- delineate_city_river("Bucharest", "Dâmbovița")  
s <- summary(bd)  
s$delineation_layers$corridor$area_km2
```

Index

* datasets

bucharest_dambovita, [5](#)
default_stac_dem, [8](#)

as.Date(), [7](#)
as_bbox, [3](#)
as_bbox(), [30](#)
as_crs, [3](#)
as_network, [4](#)

bucharest_dambovita, [5](#)

cache_directory, [6](#)
cap_corridor(), [11](#), [13](#)
check_cache, [6](#)
clean_network, [7](#)
clean_network(), [5](#), [17](#)
clear_cache, [7](#)
corridor_edge(), [11](#), [13](#)

Date, [7](#)
default_stac_dem, [8](#), [29](#)
define_aoi, [9](#)
define_aoi(), [10](#), [17](#)
delineate, [10](#)
delineate(), [17](#), [18](#), [32](#)
delineate_city_river, [12](#)
delineate_corridor, [13](#)
delineate_riverspace, [14](#)
delineate_segments, [15](#)
delineate_segments(), [11](#)
delineate_valley, [16](#)
delineate_valley(), [10](#)
delineation, [11](#), [17](#), [18](#), [32](#)

flatten_network, [17](#)

geom_delineation, [18](#)
geom_delineation(), [32](#)
get_dem, [19](#)
get_dem_example_data, [20](#)

get_osm, [21](#)
get_osm_bb, [22](#)
get_osm_buildings, [23](#)
get_osm_city_boundary, [23](#)
get_osm_example_data, [24](#)
get_osm_railways, [25](#)
get_osm_river_centerline, [25](#)
get_osm_river_surface, [26](#)
get_osm_streets, [27](#)
get_river_aoi, [28](#)
get_stac_asset_urls, [29](#)
get_stac_asset_urls(), [19](#)
get_utm_zone, [29](#)
ggplot2::coord_sf(), [18](#)
ggplot2::geom_sf(), [18](#)
ggplot2::ggplot(), [18](#)

load_dem, [30](#)

osmdata::osmdata, [31](#)
osmdata_as_sf, [31](#)

plot.delineation, [31](#)
plot.delineation(), [19](#)
print.delineation, [32](#)
print.summary.delineation, [33](#)

rcoins::stroke(), [11](#), [15](#)
reproject, [33](#)

sf::bbox, [9](#)
sf::crs, [4](#), [9](#), [34](#)
sf::sf, [4](#), [10](#), [13](#), [15](#), [16](#), [34](#)
sf::sfc, [10](#), [13](#), [15](#), [16](#), [19](#), [21](#), [24](#), [34](#)
sf::sfc_LINESTRING, [4](#), [25–27](#)
sf::sfc_MULTILINESTRING, [26](#), [27](#)
sf::sfc_MULTIPOLYGON, [11](#), [17](#), [24](#), [27](#)
sf::sfc_POLYGON, [11–13](#), [15](#), [17](#), [23](#), [24](#), [27](#),
[28](#)
sf::st_bbox(), [3](#)
sfnetworks::sfnetwork, [5](#), [7](#), [13](#), [17](#)

sfnetworks::st_network_blend(), [17](#)
sfnetworks::to_spatial_subdivision(),
 [17](#)
simplify_network(), [7](#)
summary.delineation, [34](#)
summary.delineation(), [33](#)

terra::SpatRaster, [20](#), [30](#), [34](#)
tools::R_user_dir(), [6](#)